


























Programming diagram of the LIGHT MENU




- Selecting the instrument's mode**
- DC DC voltmeter
 - PM Process monitor
 - OHM Ohmmeter
 - Pt Thermometer for sensors Pt 100/500/1 000
 - Cu Thermometer for sensors Cu 50/100
 - Ni Thermometer for sensors Ni 1 000/10 000
 - TC Thermometer for thermocouples
 - DU Display for linear potentiometer



if the mode „DU“ is not selected, these calibration menu items are left out

Only for mode „DU“


Programming diagram of the PROFI MENU



Upon delay exceeding 60 s the programming mode is automatically discontinued and the instrument itself restores the measuring mode

CONNECTING AND CONTROLLING OF INSTRUMENT

TECHNICAL DATA



Power supply cord should not be near low voltage input signal leads. Contactors, large electrical motors and other power elements should not be operated in the vicinity of the instrument. Input signal leads (measured value) should be separated from all power devices. Our instruments are extensively tested and they comply with relevant standards for use in industrial environment, however, adhering to the above mentioned measures is strongly advised.

In 'RTD' or 'OHM' input with 2-wire connection it is necessary to link the unconnected inputs (No. 5 and 6) on the terminal block

MEASURING INPUT

Input	Range	Resolution	Accuracy
DC	±90 mA	< 1 V	Input 4
	±180 mA	< 2 V	Input 4
PM	±30 mV	> 10 MΩ	Input 3
	±60 mV	> 10 MΩ	Input 3
	±1 000 mV	> 10 MΩ	Input 3
	±20 V	> 10 MΩ	Input 1
OHM	±40 V	1 MΩ	Input 1
	±80 V	1 MΩ	Input 1
	±20 mA	< 200 mV	Input 4
	±20 mA	< 200 mV	Input 4
OHM	0...100 Ω	1 MΩ	Input 1
	0...300 Ω	1 MΩ	Input 1
	0...15 kΩ	1 MΩ	Input 1
	0...3 kΩ	1 MΩ	Input 1
RTD	EU > Pt 50/100/1 000 Ω, with 3 850 ppm	-50°...450°C	Input 4
	US > Pt 100 Ω, with 3 920 ppm/°C	-50°...450°C	Input 4
Ni	Ni 1 000/ Ni 10 000 with 5 000 ppm/°C	-50°...250°C	Input 4
	Ni 1 000/ Ni 10 000 with 6 180 ppm/°C	-200°...250°C	Input 4
Cu	Cu 50/Cu 100 with 4 260 ppm/°C	-50°...200°C	Input 4
	Cu 50/Cu 100 with 4 280 ppm/°C	-200°...200°C	Input 4
T/C	J (Fe-CuNi)	-200°...900°C	Input 4
	K (NiCr-Ni)	-200°...1 300°C	Input 4
	T (Cu-CuNi)	-200°...400°C	Input 4
	E (NiCr-CuNi)	-200°...690°C	Input 4
	B (PtRh30-PtRh6)	300°...1 820°C	Input 4
	S (PtRh10-Pt)	-50°...1 760°C	Input 4
DU	R (Pt13Rh-Pt)	-50°...1 740°C	Input 4
	N (OmegaGalloy)	-200°...1 300°C	Input 4
	L (Fe-CuNi)	-200°...900°C	Input 4
	Lin. pot. supply	2.5 VDC/6 mA, min. potentiometer resistance is 500 Ω	Input 4

INSTRUMENT'S ACCURACY

TC	50 ppm/°C
Accuracy	±0,15% of the range + 1 digit ±0,3% of the range + 1 digit [T/C]
Accuracy of cold junction measurement:	±15°C
Rate	0,5...20 measurements/s
Overload capacity:	10x (t < 30 ms); 2x
Resolution	0,1°C [RTD], 1°C [T/C]
Data back-up	stores the measured value after the device has been switched off [EEPROM]
Digital filters	exponential filter, rounding
Functions	Hold - 'freezing the measured value', Tare (upon contact), Only for ranges 1 and U ≥ 2 V
External inputs	1, with the possibility of assigning various functions in the instrument's menu
OM Link	Company communication interface for operating, setting and updating of instruments
Watch-dog	reset after 500 ms
Calibration	at 25°C and 40% rh.

PROJECTION

Display	1999, red or green 7-segment LED, digit height 9,1mm
Projection	±1999
Decimal point	setting - in menu
Brightness	0 %, 25 %, 50 %, 75 %, 100 % (selectable in the menu) or automatically at three steps Auto. H, Auto. M and Auto. L

POWER SUPPLY

Power supply	10...30 VDC/24 VAC, ±10 %, 0,2...1,5 VA, isolated
--------------	---

MECHANICAL PROPERTIES


Material	Noryl GFN2 SE1, incombustible UL 94 V-1
Dimensions	48 x 24 x 72 mm
Panel cut out	43,5 x 22,5 mm

ENVIRONMENTAL

Connection	terminal board, section < 1,5 mm ²
Stabilization period	15 minutes after switch on
Working temperature	-20°...60°C
Storage temperature	-20°...85°C
Cover	IP42 (front panel only)
Construction	security class I
EL safety	EN 61010-1, A2
Dielectric strength	2,5 kVAC after 1 min between supply and input
Insulation resistance*	for pollution degree II, measuring cat. III, power supply > 300 V [PI]
EMC	EN 61326-1 (Industrial area)

*PI - Primary insulation, DI - Double insulation

MOUNTING AND DIMENSIONS



ORBIT MERRET, spol. s r.o.
Vodnanska 675/30
198 00 Praha 9
Czech republic
Tel: +420 - 281 040 200
Fax: +420 - 281 040 299
e-mail: orbit@merret.eu
www.orbit.merret.eu